











Lucere CF575

MODEL FEATURES

- 52" Blade Span
- 6-Speed Wall Control
- Integrated LED Uplight and Downlight
- 7" Downrod Included










PERFORMANCE SPECIFICATIONS

Speed	Airflow	Electricity Use	Airflow Efficiency	RPM
	Cubic Ft. Per Min.	Watts (Excl. Lights)	Cubic Ft. Per Min. Per Watt	Revolutions per Minute
High	4458	53	85	154
Low	2005	13.4	150	70

	Accepts 2.5" DR	Amps	LED Specifications			
			Lumens	Watts	CRI	CCT (K)
12°	N	0.44	Up-1400 Down-1500	Up-12 Down-18	90	3000

Control Included		Manual/Remote Reverse Switch		Downrod Length	Motor Lead Lengths
SW605	N	Wall Control	Y	7"	80"

ENERGYGUIDE INFORMATION



Energy information listed above is a weighted average of High and Low speeds.





:::: LUMINANCEBRANDS

B. Shown in Barbeque Black with Charcoal Blades and Dual Layer Opal Matte Glass Shade



C. Shown in Polished Nickel with Satin White Blades and Dual Layer Opal Matte Glass Shade



- A. LUCERE GRAPHITE
 - CF575GRT Aged Cedar Blades, Dual Layer Opal Matte Glass Shade
- B. LUCERE BARBEQUE BLACK

CF575BQ - Charcoal Blades, Dual Layer Opal Matte Glass Shade

C. LUCERE - POLISHED NICKEL

CF575PN - Satin White Blades, Dual Layer Opal Matte Glass Shade


D. Shown in Satin White with Satin White Blades and Dual Layer Opal Matte Glass Shade

D. LUCERE – SATIN WHITE

CF575SW - Satin White Blades, Dual Layer Opal Matte Glass Shade

SHIPPING SPECIFICATIONS: Carton Weight: 26.00 LBS | Length: 26.25" | Width: 12.00" | Depth: 10.75"

Product Dimensions & Weight



A. Total Fan Height: 17.3"

B. Bottom of Blade to Ceiling: 12.9"

C. Width of Housing: 8.0"

D. Width of Canopy: **6.3**"

Motor Size (mm): **153 x 18** Product Weight: **22.62** LBS

Included



SW605

6-Speed Wall Control with Canopy Mount Receiver

Optional Control



SR600

6-Speed Remote Control