


INTEGRATED LED Uplight & Downlight



Lucere CF575

MODEL FEATURES

- 52" Blade Span
- 6-Speed Wall Control
- Integrated LED Uplight and Downlight
- 7" Downrod Included


PERFORMANCE SPECIFICATIONS

Speed	Airflow	Electricity Airflow Use Efficiency		RPM	
opoor	Cubic Ft. Per Min.	Watts (Excl. Lights)	Cubic Ft. Per Min. Per Watt	Revolutions per Minute	
High	4458	53	85	154	
Low	2005	13.4	150	70	

	Accepts 2.5" DR	Amps	LED Specifications			
Pitch			Lumens	Watts	CRI	ССТ (К)
12°	N	0.44	Up-1400 Down-1500	Up-12 Down-18	90	3000

		Manual/Remote Reverse Switch		Downrod Length	Motor Lead Lengths
SW605	N	Wall Control	Y	7"	80"





ACCENT

LED LIC

BLUETOOTH* COMPATIBLE

LIFETIME MOTOR WARRANTY

Energy information listed above is a weighted average of High and Low speeds.





B. Shown in Barbeque Black with Charcoal Blades and Dual Layer Opal Matte Glass Shade




C. Shown in Polished Nickel with Satin White Blades and Dual Layer Opal Matte Glass Shade

- ass Shade hade
- A. LUCERE GRAPHITE CF575GRT - Aged Cedar Blades, Dual Layer Opal Matte Glass Shade
- B. LUCERE BARBEQUE BLACK CF575BQ - Charcoal Blades, Dual Layer Opal Matte Glass Shade
- c. LUCERE POLISHED NICKEL CF575PN - Satin White Blades, Dual Layer Opal Matte Glass Shade
- D. LUCERE SATIN WHITE CF575SW - Satin White Blades, Dual Layer Opal Matte Glass Shade

D. Shown in Satin White with Satin White Blades and Dual Layer Opal Matte Glass Shade

SHIPPING SPECIFICATIONS: Carton Weight: 26.00 LBS | Length: 26.25" | Width: 12.00" | Depth: 10.75"

Product Dimensions & Weight



A. Total Fan Height: 17.3"
B. Bottom of Blade to Ceiling: 12.9"
C. Width of Housing: 8.0"
D. Width of Canopy: 6.3"
Motor Size (mm): 153 x 18
Product Weight: 22.62 LBS

Included



SW605 6-Speed Wall Control with Canopy Mount Receiver

Optional Control



SR600 6-Speed Remote Control

 (\mathbf{M})