











Riptide CF605

MODEL FEATURES

- 52" Blade Span
- 3 ABS Blades
- Wet Location Rated
- Integrated LED Light Fixture
- 4-Speed Remote Control
- 8" Downrod










PERFORMANCE SPECIFICATIONS

	Speed	Airflow	Electricity Use	Airflow Efficiency	RPM
		Cubic Ft. Per Min.	Watts (Excl. Lights)	Cubic Ft. Per Min. Per Watt	Revolutions per Minute
	High	4507	50	91	125
	Low	1832	13.2	139	53

Blade Pitch	Accepts 2.5" DR	Amps	LED Specifications			
			Lumens	Watts	CRI	CCT (K)
Variable	N	0.5	1320	16	90	3000

Control	Receiver	Manual/Remote	Dimming	Downrod
Included	Included	Reverse Switch	Light	Length
SR401	Y	Remote	Υ	8"

ENERGYGUIDE INFORMATION



Energy information listed above is a weighted average of High and Low speeds tested with downrod supplied.





A. RIPTIDE – BARBEQUE BLACK

CF605BQ - Weather-Resistant Charcoal Blades, Opal Matte Shade

B. RIPTIDE - GRAPHITE

CF605GRT - Weather-Resistant Driftwood Blades, Opal Matte Shade

c. RIPTIDE - OIL RUBBED BRONZE

CF605ORB - Weather-Resistant Aged Oak Blades, Opal Matte Shade

D. RIPTIDE – SATIN WHITE


CF605SW - Weather-Resistant Satin White Blades, Opal Matte Shade



E. Shown in Satin White with Weather-Resistant Satin White Blades and Opal Matte Shade

SHIPPING SPECIFICATIONS: Carton Weight: 22.71 LBS | Length: 24.7" | Width: 14.80" | Depth: 12.00"

Product Dimensions & Weight



- A. Total Fan Height: 18.4"
- B. Bottom of Blade to Ceiling: 17.5"
- C. Width of Housing: 8"
- D. Width of Canopy: 7.5"

Motor Size (mm): 153 x 20 Product Weight: 19.4 LBS

Included



SR401 4-Speed Remote Control

Recommended Accessories



OPTIONAL No-Light Plates