







DUAL-MOUNT FEATURE



A. Shown in Brushed Steel with Dark Cherry Blades

Tilo CF130

MODEL FEATURES

- 30" Blade Span
- 3 Weather-Resistant Blades 4.5" Downrod
- **Dual-Mount Feature**
- 4-Speed Slide Control
- Light Fixture Adaptable (LK130)







*Certain finishes only. See fan pages for details


PERFORMANCE SPECIFICATIONS

Speed	Airflow	Electricity Airflow Use Efficiency		RPM	
	Cubic Ft. Per Min.	Watts (Excl. Lights)	Cubic Ft. Per Min. Per Watt	Revolutions per Minute	
High	2642	41	64	290	
Low	996	8	130	100	

	Accepts 2.5" DR		LED Specifications			
			Lumens	Watts	CRI	CCT (K)
12°	Y	0.4	N/A	N/A	N/A	N/A

		Manual/Remote Reverse Switch		Downrod Length	Motor Lead Lengths
SW46W	N	Manual	N/A	4.5"	42"

ENERGYGUIDE INFORMATION



speeds tested with the close to the ceiling installation method.








B. Shown in Oil Rubbed Bronze with Weather-Resistant Dark Cherry Blades



- A. TILO BRUSHED STEEL¹ CF130BS - Dark Cherry Blades
- B. **TILO OIL RUBBED BRONZE CF130ORB** Weather-Resistant Dark Cherry Blades
- C. Shown in Appliance White with Weather-Resistant Appliance White Blades and Optional Tilo Light Fixture (LK130)
- C. TILO APPLIANCE WHITE
 CF130WW Weather-Resistant Appliance White Blades

SHIPPING SPECIFICATIONS: Carton Weight: 12.00 LBS | Length: 14.75" | Width: 8.75" | Depth: 9.50"

Product Dimensions & Weight



A. Total Fan Height: 9.5"/13.3"

B. Bottom of Blade to Ceiling: 8.1"x 11.9"

C. Width of Housing: 7.3"

D. Width of Canopy: 5.1"Motor Size (mm): 153 x 10Product Weight: 10.60 LBS

Included



SW46W² 4-Speed Slide Control

Recommended Accessories Sold Separately



LK130 Light Fixture

1 Damp Location rated for ORB and WW finishes. BS is not suitable for Damp Locations.
2 Controls are recommended for indoor use only.